

**IT** Con vasca rivestita in poliuretano antiabrasivo, adatto per lavorazioni ad umido e a secco.

- Optional:**
- Variatore di velocità elettronico.
  - Coperchio insonorizzato.

**UK** With coated tank made with antiabrasive polyurethane, wet and dry system.

- Optional:**
- Electronic variable speed control.
  - Sound proof cover.

**DE** Mit Vibrationsbehälter aus einem antiabrasiven Polyurethanguss, geeignet für Trocken- und Nassbearbeitung.

- Option:**
- Stufenlose Vibrationsregulierung.
  - Schallschutzdeckel.

**FR** Avec cuve en polyuréthane anti-abrasif, convenable pour l'usage sec et humide.

- Option:**
- Variateur de fréquence électronique.
  - Couvercle insonorisé.



**OPTIONAL:**

Esempio di quadro elettrico a velocità fissa.

Example of electric board with fix speed.

Beispiel Schaltschrank mit fester Drehzahl.

Exemple du panneau électrique à vitesse fixe.



### TECHNICAL DETAILS

Mod.:	150	300	400	600	1100
• A	280	420	395	454	570
• B	240	335	365	510	550
• C	1076	1105	1500	1656	1960
• D	-	-	-	-	-
• E	870	795	1175	1152	1330
• F	830	855	900	1095	1240
• G	-	-	-	-	-
• GIRI/MIN. / R.P.M.:	1450	1450	1480	1480	1480
• MOTORE / MOTOR / MOTOR / MOTEUR:	2.5 hp	5 hp	7.5 hp	7.5 hp	10 hp
• PESO / WEIGHT / GEWICHT / POIDS:	650 kg	850 kg	900 kg	1200 kg	1400 kg

