schultheiss JEWELLERY

MC Series

Easy and reliable in-house processing of smaller volumes

Perfect mixing

Completely inert protection

Automatic casting

Maximum safety

Fast melting

Best metallurgy

		MC 300-8	MC 300-10	MC 300-12
General Specifications	Casting quantity 22 kt	3,25 kg	5 kg	7,5 kg
	Casting quantity 18 kt	2,5 kg	4 kg	6 kg
	Casting quantity AG925	1,75 kg	2,75 kg	4 kg
	Crucible size	175 ccm	275 ccm	400 ccm
	Wire	1 × 20; 2 × 7 mm	1 × 20; 2 × 7 mm	1 × 25; 2 × 10 mm
	Strip	40 × 6 mm	40 × 6 mm	50 × 8 mm
	Tube	35 mm	35 mm	45 mm
	Max. temperature	1,250°C / 1,450°C	1,250°C / 1,450°C	1,250°C / 1,450°C
	Main power	8 KVA	10 KVA	12 KVA
Casting features	secondary cooling	O	O	O
	die temp controller	O	O	O
	mixing booster	O	O	O
Control features	integrated printer / RS232	O	O	O
	system diagnose	◆	◆	◆
Security	cooling water security system	O	O	O

◆ STANDARD EQUIPMENT
O OPTIONAL FEATURE
– OPTION NOT POSSIBLE

Intergro

Intergro Co., Ltd
107-107/1 ถ.สุดประเสริฐ (ฝั่งซ้าย) แขวงบางโคล่ เขตบางคอแหลม กรุงเทพฯ 10120
107-107/1 Sudprasert Rd.(Left), Bangkhlo, Bangkholaem, Bangkok 10120 Thailand
Tel : (662) 6885080-3, Fax : (662) 688-5095, E-mail : sales@intergro.co th

www.intergro.co.th