schultheiss JEWELLERY

MG Series

Powerful and perfect metallurgy, produced in-house. For larger volumes

Perfect mixing

Completely inert protection

Automatic casting

Maximum safety

Fast melting

Best metallurgy

		MG 500-15	MG 500-20
General Specifications	Casting quantity 22 kt	9,5 kg	19 kg
	Casting quantity 18 kt	7,5 kg	15 kg
	Casting quantity AG925	5 kg	10 kg
	Crucible size	500 ccm	1,000 ccm
	Wire	1 × 30; 2 × 10 mm	1 × 30; 2 × 10 mm
	Strip	60 × 15 mm	70 × 15 mm
	Tube	45 mm	45 mm
	Max. temperature	1,250°C / 1,450°C	1.250°C / 1,450°C
	Main power	15 KVA	20 KVA
Casting features	secondary cooling	O	O
	die temp controller	O	O
	mixing booster	O	O
Control features	integrated printer / RS232	O	O
	system diagnose	◆	◆
Security	cooling water security system	O	O

◆ STANDARD EQUIPMENT
O OPTIONAL FEATURE
- OPTION NOT POSSIBLE

Intergro

Intergro Co., Ltd
107-107/1 ถ.สุดประเสริฐ (ฝั่งซ้าย) แขวงบางโคล่ เขตบางคอแหลม กรุงเทพฯ 10120
107-107/1 Sudprasert Rd.(Left), Bangkhlo, Bangkholaem, Bangkok 10120 Thailand
Tel : (662) 6885080-3, Fax : (662) 688-5095, E-mail : sales@intergro.co th

www.intergro.co.th